

**Listing of the Claims:**

The following is a complete listing of all the claims in the application, with an indication of the status of each:

---

1 1 (Currently Amended). A bus power-supply device structured to supply  
 2 power from a power-supply voltage of a node to ~~a~~ an IEEE-1394 Standard  
 3 serial bus connected to the node through a physical layer and a plurality of  
 4 connectors conducting to each other of the node, wherein  
 5 when ~~none~~ of a power supply voltage of said node is not supplied, a  
 6 DC voltage is supplied from said IEEE-1394 Standard serial bus to said  
 7 physical layer, and  
 8 when said power-supply voltage is supplied, a path for supplying a  
 9 DC voltage from said serial bus to said physical layer is cut off to supply a  
 10 DC voltage from said power-supply voltage to said physical layer and  
 11 wherein the bus power-supply device comprises:  
 12 voltage detection means for detecting said power-supply voltage  
 13 being supplied or not being supplied, and  
 14 selection means for  
 15 a) supplying a DC voltage coming from said IEEE-1394 Standard  
 16 serial bus to said physical layer in response to said voltage detection means  
 17 not detecting a power-supply voltage and  
 18 b) cutting off the path for supplying a DC voltage from said IEEE-  
 19 1394 Standard serial bus to said physical layer to supply a DC voltage  
 20 from the power-supply voltage to said physical layer in response to said  
 21 voltage detection means detecting the power supply voltage.

2 (Canceled).

1 3 (Original). The bus power-supply device as set forth in claim 1,  
 2 comprising a comparator as said voltage detection means.

1 4 (Currently Amended). The bus power-supply device as set forth in claim  
2 2 1, ~~comprising as wherein~~ said selection means comprises:  
3 a first path for supplying power from said power-supply voltage to  
4 said physical layer, and  
5 a second path for supplying power coming from said serial bus to  
6 said physical layer, wherein when power is supplied from said  
7 power-supply voltage, said second path is cut off.

1 5 (Currently Amended). The bus power-supply device as set forth in claim  
2 2 1, comprising a semiconductor switch as said selection means.

1 6 (Currently Amended). The bus power-supply device as set forth in claim  
2 2 1, comprising a comparator as said voltage detection means.

1 7 (Currently Amended). The bus power-supply device as set forth in claim  
2 2 1, comprising a relay element as said voltage detection means and said  
3 selection means.

1 8 (Currently Amended). The bus power-supply device as set forth in claim  
2 1, further comprising:  
3 a power-supply circuit for converting said power-supply voltage  
4 into a DC voltage for said serial bus and outputting the DC voltage, and  
5 voltage conversion means for converting a DC voltage output from  
6 said power-supply circuit into a DC voltage for said physical layer,  
7 ~~voltage detection means for detecting said power-supply voltage~~  
8 ~~being supplied or not being supplied to said power-supply circuit, and~~  
9 said selection means for supplying a DC voltage applied from said  
10 IEEE-1394 Standard serial bus to said voltage conversion means when said  
11 power-supply voltage is not supplied to said power-supply circuit and

AS  
12 cutting off a path for supplying a DC voltage from said IEEE-1394  
13 Standard serial bus to said voltage conversion means to supply an output of  
14 said power-supply circuit to said voltage conversion means when said  
15 power-supply voltage is supplied.

1 9 (Currently Amended). The bus power-supply as set forth in claim 8,  
2 ~~comprising as~~ wherein said selection means comprises:  
3 a first path for supplying power from said power-supply voltage to  
4 said physical layer, and  
5 a second path for supplying power coming from said serial bus to  
6 said physical layer, wherein when power is supplied from said  
7 power-supply voltage, said second path is cut off.

1 10 (Original). The bus power-supply as set forth in claim 8, wherein said  
2 voltage detection means detects said power-supply voltage being supplied  
3 or not being supplied by detecting an output voltage of said power-supply  
4 circuit.

1 11 (Original). The bus power-supply as set forth in claim 8, wherein said  
2 voltage detection means detects said power-supply voltage being supplied  
3 or not being supplied by detecting an output voltage of said power-supply  
4 circuit, and which further comprises as said selection means:  
5 a first path for supplying power from said power-supply voltage to  
6 said physical layer, and  
7 a second path for supplying power coming from said serial bus to  
8 said physical layer, wherein when power is supplied from said  
9 power-supply voltage, said second path is cut off.

1 12 (Original). The bus power-supply as set forth in claim 8, comprising as  
2 said selection means:

A8

3 a first path for supplying power from said power-supply voltage to  
4 said physical layer, and

5 a second path for supplying power coming from said serial bus to  
6 said physical layer, wherein when power is supplied from said  
7 power-supply voltage, said second path is cut off, and said selection means  
8 is structured by a semiconductor switch.

1 13 (Original). The bus power-supply as set forth in claim 8, wherein said  
2 voltage detection means detects said power-supply voltage being supplied  
3 or not being supplied by detecting an output voltage of said power supply  
4 circuit, and said selection means is structured by a semiconductor switch.

1 14 (Original). The bus power-supply as set forth in claim 8, comprising a  
2 comparator as said voltage detection means.

1 15 (Original). The bus power-supply device as set forth in claim 8,  
2 comprising a relay element as said voltage detection means and said  
3 selection means.

1 16 (Currently Amended). A node connected to a an IEEE-1394 Standard  
2 serial bus, comprising:

3 a plurality of connectors connected to the IEEE-1394 Standard  
4 serial bus each having a power-supply terminal to which a DC voltage is  
5 applied from other nodes and a signal terminal to and from which a signal  
6 from other nodes is input and output,

7 a physical layer for outputting a signal input through a signal  
8 terminal of one connector to a signal terminal of the other connector, and

9 a bus power-supply device structured to supply power from a  
10 power-supply voltage to said physical layer and said serial bus, wherein  
11 power-supply terminals of said plurality of connectors and rendered

AS

12       conductive to each other,  
 13               said bus power-supply device  
 14               supplies a DC voltage from the serial bus to said physical layer  
 15       through said power-supply terminal when none of a power-supply voltage  
 16       of said node is supplied, and  
 17               cuts off a path for supplying a DC voltage from said serial bus to  
 18       said physical layer to supply a DC voltage from the power-supply voltage  
 19       to said physical layer when said power-supply voltage is supplied, and  
 20       wherein said bus power-supply device comprises:  
 21               voltage detection means for detecting said power-supply voltage  
 22       being supplied or not being supplied to said power-supply circuit, and  
 23               selection means for  
 24               a) supplying a DC voltage applied from said IEEE-1394 Standard  
 25       serial bus to said physical layer when said voltage detection means detects  
 26       that power-supply voltage is not supplied to said power-supply circuit, and  
 27               b) cutting off a path for supplying a DC voltage from said IEEE-  
 28       1394 Standard serial bus to said physical layer to supply an output of said  
 29       power-supply circuit to said physical layer when said power-supply voltage  
 30       is supplied.

17 (Canceled).

1       18 (Currently Amended). The node as set forth in claim ~~17~~ 16, comprising  
 2       as said selection means of said bus power-supply device:  
 3               a first path for supplying power from said power-supply voltage to  
 4       said physical layer, and  
 5               a second path for supplying power coming from said serial bus to  
 6       said physical layer, wherein when power is supplied from said  
 7       power-supply voltage, said second path is cut off.

AS  
19 (Currently Amended). The node as set forth in claim 16, wherein said bus power-supply device further comprises:

a power-supply circuit for converting said power-supply voltage into a DC voltage for said serial bus and outputting the DC voltage,

voltage conversion means for converting a DC voltage output from said power-supply circuit into a DC voltage for said physical layer,

~~voltage detection means for detecting said power-supply voltage being supplied or not being supplied to said power-supply circuit, and~~

said selection means for supplying a DC voltage applied from said IEEE-1394 Standard serial bus to said voltage conversion means when said power-supply voltage is not supplied to said power-supply circuit and cutting off a path for supplying a DC voltage from said IEEE-1394 Standard serial bus to said voltage conversion means to supply an output of said power-supply circuit to said voltage conversion means when said power-supply voltage is supplied.

---